

Eur päisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 785 433 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
23.07.1997 Bulletin 1997/30

(51) Int. Cl.⁶: G01N 35/00, C12M 1/34,
B01L 3/00

(21) Application number: 96303456.6

(22) Date of filing: 15.05.1996

(84) Designated Contracting States:
BE CH DE ES FR GB IT LI

(30) Priority: 17.01.1996 US 587633

(71) Applicant: bioMerieux Vitek, Inc.
Hazelwood, Missouri 63042 (US)

(72) Inventors:
• O'Bear, Raymond E.
Granite City, Illinois 62040 (US)

• Staples, John
Florissant, Missouri 63031 (US)
• Tegeler, Garry R.
Hazelwood, Missouri 63042 (US)

(74) Representative: Froud, Clive et al
Elkington and Fife
Prospect House
8 Pembroke Road
Sevenoaks, Kent TN13 1XR (GB)


(54) Test sample card

(57) A test sample card has a fluid passage network provided on both sides of the card to provide for maximum separation distance between adjacent growth wells. The card also has cored sections along its periphery adjacent the wells, which improve the flow of plastic during the molding of the cards. The cored sections control the formation of knit lines in the surface of the card and eliminate knit lines from forming that could potentially bridge adjacent wells. These features, singly and together, combine to produce a card that is essen-

tially immune to cross-talk between adjacent wells, yet permit a greater number of wells in a card of given dimensions.

Improved bubble trap features are also provided for the card, including a bubble trap passage having a restriction formed therein. The restriction prevents air bubbles in the bubble trap from migrating back to the growth wells.

FIG.1



EP 0 785 433 A2

Descripti n

This invention relates to a test sample card; more particularly, it relates to the field of test sample cards and similar devices that hold samples for analysis by an optical system. Such sample cards are typically employed in chemical or biological sample testing systems.

Test sample cards typically have a plurality of small sample growth or reaction wells that are arranged in various arrays. The cards also have a fluid passage network that connects the growth wells to a fluid intake port. During manufacture of the card, one side of the card is taped with a clear adhesive tape to seal off one side of the wells. The individual wells are then loaded with a small quantity of chemicals or reagents, such as various growth media for bacteria, or various concentrations of different antibiotics or other drugs. After the growth wells are loaded with chemicals, the other side of the card is sealed by a clear adhesive tape, sealing the other side of the wells.

When the cards are to be put in use, the wells of the card are loaded with the sample, for example a fluid containing a biological sample from a patient. The loading of the wells may be achieved by inserting one end of a straw-like transfer tube into the fluid intake port, and placing the other end of the transfer tube into a test tube containing the sample, thereby placing the fluid intake port in fluid communication with the sample. The test tube and card/transfer tube assembly is then placed in a vacuum chamber. Vacuum is applied to the chamber and then the chamber is vented to atmosphere. The venting process causes the fluid in the test tube to enter the intake port and travel along the fluid passage network to the growth wells.

Typically, the cards are provided with a bubble trap connected to the sample well. The user orients the card such that the bubble trap is positioned above the sample well and then gives the card a light tap, causing any air bubbles in the well to move into the bubble trap.

In a microbiological testing application for the card, after the card is loaded with a sample the card is incubated for a period of time, and then read by an optical system. The optical system typically employs some form of transmittance light source that illuminates the wells of the card, and a detector arrangement that measures the transmittance of light through the wells. The amount of transmittance depends on the reaction between the sample and the growth media or drugs placed in the growth wells. The transmittance measurements for the wells of the card permits an identification of an unknown agent in the sample, or the susceptibility of the agent to different antibiotics or other drugs, or the detection of a test reaction product.

Test sample cards of the prior art include a 30-well sample card which is described in U.S. Patent No. 4,318,994 to Meyer et al. Other patents relating to the general subject of test sample cards include the Aldridge et al. patent, U.S. No. 3,963,355; the Fadler et

al. patent, U.S. No. 4,038,151; the Robinson et al. patent, U.S. No. 5,374,395; and the Charles et al. patents, U.S. Nos. 4,188,280 and 4,116,775. The Charles et al. patents also describe a card reading system for the 30-well cards described in the Meyer et al. patent.

As microbiological science has advanced over the past few decades, scientists have been able to isolate greater numbers of bacteriological agents and design suitable growth media and antibiotics for these agents. This development has resulted in a need in the art for test sample cards that have a greater number of growth wells. This need applies to both identification and susceptibility types of cards. Ideally, such a redesigned card would have the same physical dimensions and external features as the earlier generation of cards, so as to permit the redesigned card to be read by existing optical reading machines.

Placing greater numbers of wells on a card with fixed dimensions is not a simple matter of adding more wells to the cards. Rather, adding more wells to the card has the potential of increasing the possibility of inter-well cross contamination, a phenomenon known in the art as "cross-talk". Cross contamination of samples or reagents between adjacent wells can give erroneous test results when the cards are read. For example, by simply adding more wells to the 30 well card described in the above Meyer et al. patent, inter-well contamination can result. To understand the difficulty in achieving higher well counts in a card of fixed dimensions, the key issue of cross-contamination between wells and how that can affect the performance of test sample cards will be discussed in further detail.

By placing more wells on a given amount of space on the card, the wells are placed closer together. Since all the wells are indirectly in fluid communication with each other by the card's fluid channel network, cross-contamination can result from sample, growth media or reagents diffusing along the fluid channel network from one well to an adjacent well, given enough time. Some types of cards may require incubation times of up to 18 hours, which is enough time for cross-contamination to occur if the wells are too close together. Thus, increasing the number of wells in the card poses a challenge in avoiding this type of cross contamination.

In the present invention, the inventors have solved this problem by designing a fluid channel passage network that achieves a sufficient separation distance between adjacent wells (as measured along interconnecting fluid channels), while also achieving an increased areal density of wells in the card.

The inventors have also discovered that the cross-talk problem is to some extent determined by how the molten plastic flows in the card mold during the manufacture of the card. The inventors have discovered that cross-contamination can occur by virtue of the sample media travelling along very tiny fissures or cracks that can form in the surface of the cards. These cracks, known as "knot lines", are inevitably created when two flow paths of molten plastic material meet during the

card molding process. The inventors have appreciated that cross-talk can be minimized by controlling the formation in the knit lines in such a manner that they are reduced in number, and that they are oriented in a direction that is least likely to result in knit lines bridging adjacent wells.

Thus, the present invention provides design features in a test sample card that substantially reduces, if not eliminates, the probability of inter-well contamination. These features include the above-described special fluid channel networks. The invention further provides new coring techniques to improve the flow of card material during manufacture and the consequent control or elimination of knit lines that can cause inter-well contamination. Thus, the invention achieves the unexpected result of obtaining a larger number of wells per given area than prior art cards, while actually reducing the risk of cross-contamination.

The inventive test sample card possesses additional advantages and improvements. As noted above, a major issue in the design of sample cards is how the card handles the situation where air bubbles are present in the growth wells. The presence of air bubbles may be due to less than perfect vacuum conditions when the cards are loaded with samples, or as a byproduct of chemical reactions and biological processes taking place when the card is incubated with samples in the wells. The air bubbles have a tendency to distort the transmittance measurements. The invention provides for improved bubble trap and sample well features that facilitate the removal of air bubbles from the sample well into the bubble trap, and preventing of the air bubble, once in the bubble trap, from reentering the growth well. These features substantially improve the reliability of the transmittance measurements.

A test sample card is provided having a body made from a molded material, the body comprising a fluid entrance port and first and second end regions and first and second side regions. A plurality of growth or reaction wells are located in the card body between the first and second end regions and the first and second side regions. A fluid channel network connects the fluid entrance port to said growth wells. To improve the flow of the material during the molding process, cored regions are disposed in at least one of the first and second end regions or the first and second side regions. The cored regions improve the flow of the molded material during the manufacture of the card and inhibit or control the formation of knit lines in the surface of the card in a manner so as to reduce the likelihood of contamination between different wells in the card.

In a preferred embodiment, the cored region is disposed along one of the sides of the card below the identification area on the card, and includes a plurality of dam features directed towards the growth wells. The dam features help prevent the formation of knit lines in the row direction (i.e., the direction defined by the wells in a single row), which is the direction having the shortest separation distance between adjacent rows as

measured along the surface of the card. Cored features may also be formed at the ends of the card and along both sides, again helping prevent the formation of knit lines in the surface of the card and controlling the knit lines such that they form in a manner unlikely to bridge adjacent wells.

In another aspect of the invention, the card has a fluid channel network linking the fluid intake port to the wells, comprising a first set of fluid channels disposed in the top surface of the card and a second set of fluid channels disposed in the bottom surface of the card. The first and second fluid channels supply fluid to multiple wells in every row of wells in the card. The fluid channels are arranged on the card so as to increase the separation distance between adjacent wells, as measured along the fluid channels, thereby reducing the risk of contamination between adjacent wells. In a preferred embodiment, the separation distance is greater than or equal to one inch in a card measuring roughly 3 1/2 inches by 2 1/4 inches.

In yet another aspect of the invention, at least one of the wells has a bubble trap in communication with the well via a bubble trap passage. The bubble trap passage has a well end and a bubble trap end, wherein the width of the well end of the bubble trap passage is greater than the width of the bubble-trap end of the bubble trap passage. This funnel-shaped bubble trap passage promotes the collection of air bubbles in the bubble trap. At the intersection of the walls forming the bubble trap passage and the bubble trap, a restriction is formed in the bubble trap passage. The restriction, preferably in the shape of a sharp corner, prevents any air bubbles in the bubble trap from migrating from the bubble trap back into the growth well.

A further embodiment of the invention provides for raised rail features along the sides of the card, which facilitate the stacking of cards without scuffing of the adhesive tape covering the cards. The scuffing can interfere with the optical measurements, and if serious enough, could disturb the adhesive tape and increase the possibility of inter-well contamination.

An object of the invention is to provide a test sample card with a reduced probability of cross-talk from adjacent growth wells.

A further object of the invention is to provide card molding features which control knit lines and prevent them from forming in a manner that could contribute to cross-talk.

A further object of the invention is to provide a test sample card that has a bubble trap passage that facilitates the collection of bubbles in a bubble trap, and prevents the bubbles from leaving the bubble trap and reentering the growth wells.

Presently preferred embodiments of the invention are depicted in the drawings, wherein like reference numerals refer to like elements in the various views, and wherein:

Figure 1 is a plan view of the bottom side of the

card;

Figure 2 is a plan view of the top side of the card;

Figure 3 is a side view of the card;

Figure 4 is a side view of the card opposite to the side of Figure 3;

Figure 5 is an end view of the card;

Figure 6 is an end view showing the opposite end of Figure 5;

Figure 7 is a detailed plan view of the wells of the card that receive fluid samples from the through-card feed channels of Figure 2;

Figure 8 is a detailed plan view of the wells of the card that receive sample fluid from the feed channels in the bottom surface of the card;

Figure 9 is a sectional view of the wells along the lines 9-9 of Figures 7 and 8;

Figure 10 is a sectional view of the bubble trap along the lines 10-10 of Figures 7 and 8;

Figure 11 is a sectional view along lines 11-11 of the through-card feed channel of Figure 7;

Figure 12 is an enlarged plan view of the bubble trap passage showing the relationship between the dimensions of the entrance and restriction portions of the bubble trap passage; and

Figure 13 is a plan view of a portion of the card shown greatly enlarged in order to illustrate how the cored sections control the formation of knit lines in the surface of the card.

Figure 1 shows the bottom surface 12 of a preferred test sample card 10 in accordance with a preferred embodiment of the invention. The surface 12 is referred to as the "bottom" due to the fact that it receives clear adhesive tape first, and is placed face down during the loading of the wells with growth media or other chemicals or reagents. The card 10 has a rear edge 13, a front edge 15 and a top surface 14 shown in a plan view in Figure 2. Preferably, the card 10 is manufactured using an injection molding process from crystal polystyrene, such as Dow Chemical Company Styron™ 666D crystal polystyrene, or the equivalent.

Referring to Figures 1, 2 and 4, a fluid intake port 16 is located on the side of the card 10 which provides an opening for fluid containing biological or control or chemical samples to enter into the interior of the card 10. The port 16 is connected to a fluid intake passage 17 that leads to an intake manifold 18.

A fluid channel network 20 comprising a pattern of full-radius, shallow (e.g., 0.012 inches deep) grooves, is provided on the bottom surface 12. During the card loading process, fluid travels from the intake manifold 18 along the network 20 to a plurality of growth wells 26 arranged in an array in the card 10. The fluid passage network 20 includes primary fluid channels 22A and 22B extending horizontally to the left and right, respectively, of the manifold 18; a set of secondary fluid channels 24 extending upwardly from the fluid channels 22A and 22B; and a set of ternary fluid channels 25 which lead from the secondary channels 24 to the growth

wells 26.

Each of the growth wells 26 contains a bubble trap 28 which is in communication with the growth wells 26 by a bubble trap passage 70. The bubble traps 28 and bubble trap passages 70 are discussed in detail in conjunction with Figures 7-12 below.

As shown in Figures 1 and 6, the card 10 has a pair of opposed gripping slots 40 at the front end 15 of the card, which are gripped by mechanical structures in the card reader (not shown) for the card 10. Other gripping features could be provided for other types of readers. A pair of positioning notches 42 are provided in the front edge 15 of the card, which assist in the placement of the card 10 in proper alignment with the optical system for the card reader. A tray keeper notch 44 is provided along the side of the card 10 adjacent to the port 16. As shown in Figures 2, 3, and 6, an alignment groove 52 is provided on the bottom surface of the card to insure that the user correctly inserts the card in the reading machine. Alternative insertion and orientation features could of course be provided.

The top surface of the card 10 is shown in Figure 2, and includes a second set of fill channel grooves 62 in communication with the manifold 18. The fill channels 62 each terminate in a through-card feed channel 30, which passes through the card 10 from the top side of the card shown in Figure 2 to the bottom side of the card 10 shown in Figure 1. The through-card feed channel 30 conducts fluid samples to a fill channel 76, shown in Figures 1 and 7. The fill channels 76 conduct sample fluid into the growth wells 26.

Referring now to Figure 7, the growth wells 26 that receive fluid samples from the through-card feed channels 30 are shown in greater detail. The through-card feed channel 30 is shown in a vertical cross-sectional view in Figure 11. The fluid sample passes through the card 10 from the top side of the card (Figure 2) to the bottom side of the card (Figure 1) via the through-card feed channel 30, and then enters a fill channel 76. The fill channel 76 leads to the bottom portion 75 of the well 26.

From Figures 1 and 2, it can be seen that fluid channels are provided on both sides of the card 10. In particular, from Figures 1 and 2 it can be seen that the fluid channels on both sides of the card 10 provide an inter-well separation distance of at least one inch in a card with dimensions of approximately 3 1/2 inches by 2 1/4 inches, with the inter-well separation distance measured along the fluid channels that connect the wells together. For example, referring to the left hand side of the top surface of the card (Figure 2), fluid channel 62A provides a pathway for sample fluids to the growth well 26A via the through-card feed channel 30A. Well 26A is in communication with well 26B via channel 30A, fluid passages 62A and 62B, and channel 30B. By virtue of the elongate fluid channels 62A and 62B, the inter-well separation distance of wells 26A and 26B is on the order of an inch and half in the illustrated embodiment. The separation distance is sufficiently great that

the probability of inter-well contamination along the passages 62A and 62B is exceedingly remote, even with a long incubation time for the card. For most microbiological applications, in which the sample remains in the wells for some time during incubation and reading, a minimum desirable separation distance as measured along the fluid channels is at least 0.75 inches, with at least one inch preferred. The greater the separation distance, the less likely that diffusion of fluids or reagents between wells along the fill channels will occur.

Referring to the right-hand side of Figure 1, a potential cross-contamination pathway exists between wells 26C and 26D via fluid channels 23, 22B, 24A and 25A. However, the channels 23, 22B, 24A and 25A are designed such that the distance from well 26C to well 26D is greater than one inch, substantially reducing the possibility of inter-well contamination. The channel 23 is given an "S" shape to increase the distance from the channel 22B to the well 26C. Note further that well 26D has a potential cross-contamination pathway with well 26E via fluid channels 25A and 24A but this distance again is at least an inch in the illustrated embodiment, substantially eliminating the likelihood of inter-well contamination between wells 26E and 26D.

As can be seen from Figures 1 and 2, the wells 26 in the card are arranged in an array of multiple rows of wells 26, each of the rows of wells having a common fluid channel network described for the row 33 adjacent to the end 13 of the card.

As shown in Figure 2, an identification area 50 is provided on the surface 14 of the card 10. The area 50 includes a series of "8"s which provide an area for a technician to write identification numbers associating the test sample card 10 with the particular patient or test. A card code block 51 is placed adjacent the area 50 and includes eleven identification blocks identifying the type of card depending on how the blocks are marked. An external test result (ETR) mark location 55 is also provided on the top surface.

Referring to Figure 1, the card 10 further includes a first row 31 adjacent to end 15. A set of oval-shaped cored pockets 32 are provided having a major axis MA (Figure 1) oriented towards the adjacent row 31 of wells 26. The molten plastic card material enters the mold at the molding gate region 21. The cored pockets 32 enhance the flow of the material during the molding of the cards 10. Specifically, the mold for the cards has positive elements that create the cored pockets 32 to help prevent the formation of knit lines adjacent to the first row 31 of wells 26 and prevent the formation of knit lines in the direction along the major axis MA (Fig. 2) of the wells 26 (i.e., the row direction where the separation distance between the wells measured along the surface of the card is the least). Referring to Figure 2, a set of oval cored pockets 54 are also provided to reduce the possibility of knit lines being formed adjacent to the last row 33 of wells 26 in a manner parallel to the major axis of the wells. A preferred depth of the cored pockets 32 and 54 (height of the positive elements) is 0.07 inches,

but this depth is not especially critical.

While oval shaped cored pockets are illustrated, other shapes could be used. Preferably, the shapes are either oblong or elongate with the long axis of the pocket oriented towards the adjacent row of wells, as shown in the example of oval pockets in Figures 1 and 2. This promotes a flow of molten plastic and control of knit lines such that the knit lines form, if at all, in a manner roughly parallel to the long axis of the pocket: the direction in which the inter-well separation distance as measured along the surface of the card is the greatest.

The side of the card 10 adjacent to the primary fluid channel 22A and 22B also contains cored sections 36 and 38. These cored sections control the formation of knit lines on the surface of the card 10 during the molding of the card, particularly in the vicinity adjacent to the first column of wells immediately adjacent to the primary fluid channels 22A and 22B.

Another cored section 34 is provided on the opposite side of the card as shown in Figure 1, adjacent to the wells 26 in the far column of wells. The cored section 34 is preferably between 0.020 and 0.050 inches, so as to not interfere with the reading of the identification marks on the top surface of the card. A preferred depth of the cored section 34 is 0.030 inches. The cored section 34 is located on the bottom side of the card as shown in Figure 1 directly behind the identification area 50, shown in Figure 2. With a depth of 0.030 inches, the reading of the identification information in the regions 50, 51, 55 by an optical system in the card reader is not adversely affected.

The cored section 34 improves the flow of molten plastic material over the card during the manufacture of the card, and controls the formation of knit lines in the surface of the card. As shown in Figure 1, the cored section 34 preferably includes a set of V-shaped dam portions 35 which improve the flow of the material during the molding of the card 10. The dam portions 35 (comprising extensions of the cored section 24 with a recess of, for example 0.03 inches) prevent knit lines from forming in a direction parallel to the major axis of the wells 26, where the separation distance (as measured along the surface of the card) is the least. Instead, the knit lines form, if at all, generally parallel to the minor axis of the wells, and thus are unlikely to bridge two wells.

In accordance with the above, persons of skill in the art of plastic molding will appreciate that the mold for manufacturing the test sample card has positive elements that create the recessed cored sections 32, 34, 54, 60 and the dam feature 35. For the cored sections 32, the positive elements comprise a set of an elongate oval elements positioned adjacent to the elements that define the rows of wells. The elongate elements have a major or long axis MA oriented perpendicular to the row direction. The positive elements direct the flow of card material in the mold during molding in a manner so as to control the formation of knit lines in the surface of the card.

Referring to Figure 13, a portion of the bottom side 12 of the card 10 is shown enlarged in order to illustrate the how the cored sections control the formation of knit lines. The card material enters the mold at the gate 21. The knit lines 81 are tiny fissures (also exaggerated in thickness in Figure 13) that form when plastic flows from the gate around the positive elements that form the cored sections 32. The flow of plastic in the mold is such that the knit lines 81 in the surface 12 of the card tend to form in a direction generally perpendicular to the well major axis MWA, which is the direction in which the inter-well separation distance (measured along the surface of the card) is the least. The same effect is achieved by the other cored sections in the card, including the dam features 35 in the cored section 34.

Referring to Figures 7 and 9, the card portion 78 surrounding the well 26 includes a slanted wall portion 72 that cooperates with wall 77 to form a generally funnel-shaped region in the bubble trap passage 70. The funnel-shape bubble trap passage 70 includes a restriction 74 comprising a sharp corner at the intersection of the bubble trap passage 70 and the bubble trap 28. In use, when the sample fluid enters the card and fills the well 26, the technician holds the card 10 in a position such that the bubble traps 28 are generally in an upward or vertically inclined position relative to the wells 26. The technician jiggles the card with a tap or a snap of the wrist, jiggling any air bubbles that may be present within the well 26 into the bubble trap 28. Taking advantage of the surface tension and meniscus properties of the sample fluid, the sharp corner restriction 74 serves to prevent any air bubbles that may be present in the bubble trap 28 from re-entering the well 26.

The geometry of the bubble trap passage 70 is shown schematically in Figure 12. At the intersection of the bubble trap passage 70 and the bubble trap 28, the width between the restriction 74 and the wall 77, W1, is less than 0.04 inches, with 0.033 inches in a preferred embodiment. At the entrance of the bubble trap passage, the width between the corner 79 and the wall 77, W2, is greater than W1 and 0.066 inches in the preferred embodiment. The relatively wide distance W2 allows air bubbles in the well 26 to be slinged into the bubble trap passage 70 and the bubble trap 28 when the card is tapped by the user. The narrow restriction at W1, and especially the sharp restriction corner 74, prevents the air bubble from migrating out of the bubble trap 28 and back into the well 26.

Referring to Figure 8, the construction of the wells that receive fluid samples along the fluid channels 25 is the same as that described in Figures 7 and 9. Referring to Figure 10, the bubble trap 28 is shown in a sectional view along the lines 10-10 of Figures 7 and 8.

An additional feature to the card 28 is a rail feature that is used to separate cards from each other when the cards are stacked. This rail feature is especially useful when the cards are ejected from the mold and stacked on top of each other. The separation of the cards prevents any scuffing of the surface of the cards. After tape

has been applied to the cards, the rails also prevent possible damage to the adhesive tape applied to the cards. Referring to Figures 2, 5 and 6, a pair of raised rail features 60 are provided on opposite edges of the card on one side of the card. The raised rail features 60 extend along substantially the entire length of the card 10. The height of the raised rails 60 need only be enough to prevent the adhesive tape covering the wells from touching when the cards are stacked. A height of 0.006 inches or thereabouts for the rail features 60 is sufficient for the illustrated embodiment. The ramp features 61 facilitate the stacking operation by allowing the rails to slide over each other as the cards are slid into a stacked condition.

Preferred sample loading and reading machines for the card are available from bioMérieux Vitek, Inc., 595 Anglum Drive, Hazelwood, Missouri.

From the forgoing, it will be appreciated that some modification may be made from the preferred embodiment without departure from the scope of the invention. For example, the location of the cored sections in the card may be modified somewhat depending on the particular material chosen from the card, the location of the wells, and the dimensions of the card. Further, the particular fluid channel design in the top and bottom surfaces of the card may be varied. For example, the channels could be designed in an alternating pattern, such that every other well in a row of wells receives fluid samples from fluid channels in the top and bottom surfaces of the card, thereby achieving an adequate inter-well separation distance.

Claims

1. A test sample card comprising a body made from a molded material, the said body comprising a fluid entrance port and first and second end regions and first and second side regions, the said body defining a plurality of wells placed between the said first and second end regions and the said first and second side regions, the said body further comprising a fluid passage network connecting the said fluid entrance port to the said wells, characterised in that the said body has cored regions disposed in at least one of the said first and second end regions or the said first and second side regions, which cored regions improve the flow of the said molded material during the manufacture of the said card and inhibit the formation of knit lines in the said material so as to reduce the likelihood of contamination between different wells in the said card.
2. A card as claimed in claim 1 wherein the said cored regions are disposed in at least one of the said first and second end regions of the said card, the said wells (preferably 45) are arranged in a plurality of parallel rows having a first row adjacent to the said first end region and a last row adjacent to the said second end region, and the said cored regions

- comprise a first set of cored pockets oriented across the said first end region substantially parallel and adjacent to the said first row and a second set of cored pockets oriented substantially parallel and adjacent to the said last row, preferably the said first and second cored pockets comprising elongate oval coring pockets defining an major axis arranged such that the major axis is oriented perpendicular to the said first and last rows.
3. A card as claimed in claim 1 or claim 2 wherein the said cored regions are disposed in at least one of the said first and second side regions and the said cored regions comprise at least one dam portion disposed at the boundary of the said cored region and the non-cored portion of the said card.
 4. A card as claimed in any of claims 1 to 3 wherein the said card has a top surface and an identification region in the said top surface, and a bottom surface and a cored region in the said bottom surface the said identification region, preferably the said card being made from injection molded crystal polystyrene.
 5. A card as claimed in any of claims 1 to 4 wherein the said cored region has a depth of between 0.02 and 0.05 inches, preferably substantially 0.03 inches.
 6. A test sample card comprising a body comprising a fluid entrance port and first and second end regions and first and second sides regions, the said body defining a plurality of wells placed between the said first and second end regions and the said first and second side regions, the said body further comprising a fluid passage network connecting the said fluid entrance port to the said wells, characterised in that at least one of the said wells has a bubble trap in communication with the said well via a bubble trap passage, the said bubble trap passage having a well end and a bubble trap end, the width of the said well end being greater than the width of the said bubble trap end, and the intersection of the said bubble trap end of the said bubble trap passage and the said bubble trap forming a restriction in the said bubble trap passage, the said bubble trap passage facilitating the collection of air bubbles which may be present in the said wells in the said bubble trap and the said restriction preventing air bubbles from migrating from the said bubble trap into the said well.
 7. A card as claimed in claim 6 wherein the said well comprises a first end portion and an opposite second end portion, the said bubble trap being located adjacent to the said first end portion and a fluid entrance passage entering the said well at the said second end portion.
 8. A card as claimed in claim 6 or claim 7 wherein the said restriction comprises a sharp corner at the intersection of the said bubble trap passage and the said bubble trap, the said sharp corner preventing bubbles from moving from the said bubble trap into the said bubble trap passage and into the said well.
 9. A card as claimed in any of claims 6 to 8 wherein the said fluid passage network connects the said fluid entrance port with the said well by fluid channels disposed on the front and rear surfaces of the said card thereby to increase the separation distance between adjacent wells.
 10. A test sample card comprising a body comprising a fluid entrance port and first and second end regions and first and second side regions, the said body defining a plurality of growth wells placed between the said first and second end regions and the said first and second side regions, the said body further comprising a top surface and a bottom surface and a fluid passage network connecting the said fluid entrance port to the said growth wells, characterised in that the said fluid passage network comprises a first set of fluid channels disposed in the said top surface of the said card and a second set of fluid channels disposed in the said bottom surface of the said card, the said first and second sets of fluid channels being arranged on the said card so as to provide an adequate separation distance between adjacent wells as measured along the said fluid channels thereby reducing the risk of contamination between adjacent wells.
 11. A card as claimed in claim 10 wherein the said separation distance is greater than 0.75 inches, preferably greater than 1 inch.
 12. A card as claimed in claim 10 or claim 11 wherein the said wells are arranged in a series of rows in the said card with five wells per row, and the said fluid channels between the said port and the said five wells of the said row are disposed in the said top and bottom surfaces of the said card such that two fluid channels are disposed on one of the said surfaces of the said card leading to two of the said wells in the said row of wells and three fluid channels are disposed on the other of the said surfaces to the remaining three of the said wells in the said row of wells, preferably the said fluid channels being disposed in the said top and bottom surfaces of the said card substantially as illustrated in accompanying Figures 1 and 2.
 13. A test sample card characterised in that it comprises: top and bottom surfaces;
 - a body defining a plurality of wells;
 - a fluid entrance port in the said body;

a fluid channel network disposed in the said top and bottom surfaces of the said card connecting the said fluid entrance port with the said wells;

at least one cored region adjacent to the said wells; and

each of the said wells comprising a bubble trap and a bubble trap passage connecting the said well to the said bubble trap, the said bubble trap passage having a well end and a bubble trap end, the width of the said well end being greater than the width of the said bubble trap end and the intersection of the said bubble end of the said bubble trap passage and the said bubble trap forming a restriction in the said bubble trap passage, the said bubble trap passage facilitating the collection of air bubbles which may be present in the said wells in the said bubble trap and the said restriction preventing air bubbles from migrating from the said bubble trap into the said well.

14. A card as claimed in claim 13 wherein the said card comprises an array of wells arranged in a series of rows, each of the said rows having at least one well receiving fluid from the said sample port by a fluid channel in the said top surface of the said card and at least one well receiving fluid from the said sample port by a fluid channel in the said bottom surface of the said card.

15. A card as claimed in claim 13 or claim 14 wherein the said bubble trap passage comprises a slanted passage wall and the said bubble trap comprises a cylindrical wall forming the said bubble trap, the said restriction comprising a sharp corner at the intersection of the said cylindrical wall and the said slanted passage wall.

16. A test sample card comprising a body having a top surface and a bottom surface, adhesive tape being applied to the said top and bottom surfaces, a fluid entrance port and first and second end regions and first and second side regions, the said body defining a plurality of wells placed between the said first and second end regions and the said first and second side regions, the said body further comprising a fluid passage network connecting the said fluid entrance port to the said wells, characterised in that it comprises a pair of rails upwardly extending from one of the said top or bottom surfaces, the said rails permitting the said cards to be stacked without touching of adhesive tape applied to adjacent cards in the said stack of cards.

17. A card as claimed in claim 16 wherein the said rails are oriented along the said first and second side regions between the said ends of the said card.

18. An apparatus characterised in that it comprises:

a bubble trap for collecting air bubbles from a sample well; and
a bubble trap passage interconnecting the said bubble trap to the said sample well;
the said bubble trap passage comprising a funnel-shaped channel and having a restriction formed therein, the said restriction preventing air bubbles collected in the said bubble trap from returning to the said sample well.

19. An apparatus as claimed in claim 18 wherein the said restriction is located at the intersection of the said bubble-trap passage and the said bubble trap, and preferably comprises a sharp corner.

20. An apparatus as claimed in claim 18 or claim 19 wherein the said restriction in the said bubble trap passage has a width, W1, of less than 0.04 inches.

21. A mold for manufacturing a test sample card from a card material characterised in that it comprises a plurality of sample wells, the said card having an exterior surface after ejection of the said card from the said mold, the said mold having at least one positive element creating at least one cored section in the said card adjacent to the said wells, the said positive element directing the flow of the said card material in the said mold so as to control the formation of knit lines in the surface of the said card substantially to prevent the said knit lines from forming in a predetermined direction.

22. A mold as claimed in claim 21 wherein the said wells are arranged in a plurality of rows defining a row direction and the said positive element comprises an elongate element positioned adjacent to the said rows and having a long axis oriented perpendicular to the said row direction, preferably the said positive element comprising a dam feature located adjacent to the said wells.

FIG.1




FIG. 2




FIG. 3




FIG. 4




FIG. 5



FIG. 6




FIG.7




FIG.8




FIG.9




FIG.10




FIG.11







FIG.12

FIG. 13



THIS PAGE BLANK (USPTO)



Eur päisches Patentamt
Eur pean Patent Office
Office européen des brevets



(11) EP 0 785 433 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
29.12.1997 Bulletin 1997/52

(51) Int. Cl.⁶: G01N 35/00, C12M 1/34,
B01L 3/00, B29C 45/00

(43) Date of publication A2:
23.07.1997 Bulletin 1997/30

(21) Application number: 96303456.6

(22) Date of filing: 15.05.1996

(84) Designated Contracting States:
BE CH DE ES FR GB IT LI

(30) Priority: 17.01.1996 US 587633

(71) Applicant:
bioMerieux Vitek, Inc.
Hazelwood, Missouri 63042 (US)

(72) Inventors:
• O'Bear, Raymond E.
Granite City, Illinois 62040 (US)

• Staples, John
Florissant, Missouri 63031 (US)
• Tegeler, Garry R.
Hazelwood, Missouri 63042 (US)


(74) Representative:
Froud, Clive et al
Elkington and Fife
Prospect House
8 Pembroke Road
Sevenoaks, Kent TN13 1XR (GB)

(54) Test sample card

(57) A test sample card has a fluid passage network provided on both sides of the card to provide for maximum separation distance between adjacent growth wells. The card also has cored sections along its periphery adjacent the wells, which improve the flow of plastic during the molding of the cards. The cored sections control the formation of knit lines in the surface of the card and eliminate knit lines from forming that could potentially bridge adjacent wells. These features, singly and together, combine to produce a card that is essen-

tially immune to cross-talk between adjacent wells, yet permit a greater number of wells in a card of given dimensions.

Improved bubble trap features are also provided for the card, including a bubble trap passage having a restriction formed therein. The restriction prevents air bubbles in the bubble trap from migrating back to the growth wells.



EP 0 785 433 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 96 30 3456

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	US 4 318 994 A (MEYER MICHAEL C ET AL) 9 March 1982 * column 2, line 3 - line 5 * * column 2, line 20 - line 25 *	1	G01N35/00 C12M1/34 B01L3/00 B29C45/00
A	* column 4, line 59 - column 5, line 12; figures 3,4 *	6,7	
A	EP 0 526 222 A (SONY CORP) 3 February 1993 * column 13, line 30 - column 14, line 21; figure 12 *	1	
A	US 3 880 978 A (APOSTOLERIS THEODORE G ET AL) 29 April 1975 * column 2, line 11 - line 27 * * column 3, line 62 - line 65 * * column 4, line 68 - column 6, line 38; figures *	1	
A	* column 3, line 13 - line 55 *	21	
P,A	EP 0 703 052 A (RHYTHM WATCH CO) 27 March 1996 * column 2, line 5 - line 13; figures 2,6 *	1	TECHNICAL FIELDS SEARCHED (Int.Cl.6)
	* column 2, line 39 - line 48 * * column 4, line 53 - column 5, line 2; figure 4 *		B29C
A	& TW 246 742 A (RHYTHM WATCH CO) 1 May 1995	1	
A	WO 94 18369 A (MAYTAG CORP) 18 August 1994 * page 6, line 15 - line 19 * * page 8, line 1 - line 4 * * page 10, line 4 - line 12 * * page 11, line 8 - page 12, line 5; figures *	1	
-/--			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 October 1997	Examiner Hocquet, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 96 30 3456

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	GLENN BEALL: "plastic part design part 3" DESIGN ENGINEERING., September 1985, LONDON GB, pages 75-80, XP002036568 * page 75; figure 2 *		
E	EP 0 745 856 A (BIOMERIEUX VITEK INC) * column 2, line 18 - line 21; claims 10,12 * * column 4, line 6 - line 17 * * column 5, line 15 - line 26 * * column 5, line 58 - column 6, line 18 * * column 6, line 48 - column 7, line 5 *	10,11	
T	* page 9, line 10 - line 22 *	16,17	
A	EP 0 282 840 A (BECTON DICKINSON CO) * column 5, line 9 - line 32; figures 1-3 *	10	
A	US 4 074 940 A (TARBET CECIL SIDNEY CHARLES) * column 3, line 34 - line 46; claim 2; figures 1,2 *	6,7,13,18	TECHNICAL FIELDS SEARCHED (Int.Cl.6)
Y	FR 2 350 593 A (MC DONNELL DOUGLAS CORP) * page 2, line 8 - line 12 * * page 7, line 31 - page 8, line 11; figures 2,3 * * column 15, line 23 - line 31; figure 1 *	16,17	
Y	FR 2 368 774 A (ABBOTT LAB) * page 1, line 21 - line 34 * * page 2, line 33 - page 3, line 10; figures 3-5 * * page 3, line 23 - line 26 *	16,17	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 October 1997	Examiner Hocquet, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04C01)

THIS PAGE BLANK (USPTO)